

Product datasheet: LI Battery Fire Suppression Kit 320Wh (PRO4631)

KMA GROUP

Contents

- Carrying bag/rucksack
- Fire extinguisher 2L AVD Lith-Ex
- Gloves (pair)
- Instructions card



The manufacture and supplier reserve the right to change the design and/or specification without prior notice.

Important notice: The datasheet contains typical information specific to products manufactured at the time of its publication.

©KMA Group BV – Contents herein do not constitute a warranty.

Specifications

Carrying bag/rucksack	
Dimensions rolled up (mm):	550x270x100
Dimensions open (mm):	680x540
Weight:	2.1 kg
Temp. resistance inner lining:	1000°C+
Insulating middle layer:	1000°C+
Outside layer:	400°C+

Extinguisher	
Capacity:	2 Liter
Extinguishing agent:	AVD*
Weight agent:	2.2 kg
Total weight:	3.9 kg
Total height:	410mm
Total diameter:	110mm
Min. operating temp.:	+5°C
Max. operating temp.:	+60°C
Discharge time (appr.):	50 sec
Propellant N2:	15 Bar (20°C)
Fire class/rating:	5A

Gloves	
Temp. Resistance:	180°C
Norm:	EN388 EN407
Material:	Nitrilrubber